


Application Data Sheet:

PAVACRYL

HARD COAT



APPLICATION:

- **ALWAYS TEST PRODUCT ON A SMALL AREA FIRST** and allow a 24 hour cure time to determine the ease of application and desired results for both stain resistance and appearance that will meet YOUR requirements.
- Allow new concrete to cure for at least 14 days prior to application.
- Remove all dirt, stains, dust and foreign material.
- Colored concrete should be wet down then 30 parts water to 2 parts hydrochloric acid mixture applied, scrubbed lightly and thoroughly rinsed off.
- For non colored concrete, the same should be done with 20 parts water to 1 part hydrochloric acid solution.
- If an unsealed surface gets wet, allow 24 hours for drying.
- Initial coat 4 - 8 square meters and second coat 7 - 10 square meters per litre, depending on the porosity of the substrate.
- Use a brush, broom or roller.
- For colored concrete or especially smooth concrete, we recommend that the first coat of sealer be diluted with 20% **EVERSOL**.
- 1 or 2 coats should be applied depending on the finish required and the porosity of the substrate.
- Application should not be made when temperature is over 30°C.
- **PAVACRYL** can reduce the non-slip characteristic of a surface, particularly when the surface is smooth. We recommend the use of '**GRIP ENHANCER**' mixed with **PAVACRYL**.
- If using as a COLOR ENHANCER for SANDSTONE it is best to pre-seal area with **SILCOPEL** or **CONSOLIDATE** for best results. Allow pre-sealer 24 - 48 hours to cure before applying **PAVACRYL**.

Disclaimer – User Guide

*Solutions - Sealers for Stone & Tile believes the information contained in this document is accurate as **general advice only**. As general advice only it has been prepared without taking into account the objectives, problems or needs of the reader. Solutions – Sealers for Stone & Tile has presented this information as a guide only and accepts no liability for any loss or damage caused by any error in, or omission from, this document. Solutions – Sealers for Stone & Tile has no control over the use or misuse of this product, therefore no warranty expressed or implied shall be given. Solutions – Sealers obligations shall be limited to only replacing product PROVEN defective. The user **MUST** educate themselves on the performance value, application rates, substrate type and environment before product is applied, a **TEST** area is always highly recommended.*

Technical Data Sheet:

PAVACRYL

HARD COAT



Description:

PAVACRYL is an extra tough clear acrylic sealer especially designed for concrete and sandstone. Excellent resistance to heavy wear and ultra violet rays makes **PAVACRYL** ideal for external high traffic areas such as industrial and residential driveways, as well as paths, patios, pool surrounds, garages, shed.

Advantages:

- Suitable for internal and external use
 - Finishes extremely hard for excellent wearing under heavy traffic
 - High solids contents for ease of coverage of porous surfaces such as concrete and pavers
 - Gives surface a glossy wet look, and enhances the natural colors of the surface.
 - Seals against food, soils, grease, oil and inhibits staining
 - Seals lime dust into concrete to prevent leaching and a constant need for sweeping
 - Is easy to reseal without stripping
 - Does not yellow externally
 - Australian owned and manufactured in Australia
-

Characteristics:

Colour:	Clear
Weight:	0.90
Solvent:	Hydrocarbon
DG Class:	3
U.N Number:	1263
Coverage:	4 – 8 sq m per lt (depending on porosity)

Recommendations:

Sandstone
Exposed aggregate
Plain concrete
Concrete Pavers
Stamped Concrete
Stencil Concrete

Disclaimer – User Guide

*Solutions - Sealers for Stone & Tile believes the information contained in this document is accurate as **general advice only**. As general advice only it has been prepared without taking into account the objectives, problems or needs of the reader. Solutions . Sealers for Stone & Tile has presented this information as a guide only and accepts no liability for any loss or damage caused by any error in, or omission from, this document. Solutions . Sealers for Stone & Tile has no control over the use or misuse of this product, therefore no warranty expressed or implied shall be given. Solutions . Sealers obligations shall be limited to only replacing product **PROVEN** defective. The user **MUST** educate themselves on the performance value, application rates, substrate type and environment before product is applied, a **TEST** area is always highly recommended.*

