

Application Data Sheet:

SILACRYL

WET LOOK & MATT FINISH

APPLICATION:

- **ALWAYS TEST PRODUCT ON A SMALL AREA FIRST** and allow a 24 hour cure time to determine the ease of application and desired results for both stain resistance and appearance that will meet YOUR requirements.
- Remove all dirt, oil, wax, stains, dust, efflorescence, grout haze and flaking material. Ensure any acid or detergent used is hosed off completely.
- Allow newly laid concrete to cure for at least 28 days prior to application.
- If an unsealed surface has been wetted, allow 24 hours prior to sealing.
- Stir well before use.
- Use a brush, broom, spray or lambs wool applicator.
- Apply two to three coats depending on the finish required and the porosity of the substrate.
- For dense surfaces or where slate is laminating the first coat of **SILACRYL** should be broken down with 50 % **EVERSOL** or **TOLUOL**. This will improve the penetration and subsequent adhesion.
- Application should not be done when temperature is $>30^{\circ}\text{C}$.
- **SILACRYL** is designed to seal and protect and may increase the tendency to slip on some surfaces especially when wet. Test and add '**GRIP ENHANCER**' to the final coat if required.


Disclaimer – User Guide

Solutions - Sealers for Stone & Tile believes the information contained in this document is accurate as **general advice only**. As general advice only it has been prepared without taking into account the objectives, problems or needs of the reader. Solutions – Sealers for Stone & Tile has presented this information as a guide only and accepts no liability for any loss or damage caused by any error in, or omission from, this document. Solutions – Sealers for Stone & Tile has no control over the use or misuse of this product, therefore no warranty expressed or implied shall be given. Solutions – Sealers obligations shall be limited to only replacing product **PROVEN** defective. The user **MUST** educate themselves on the performance value, application rates, substrate type and environment before product is applied, a **TEST** area is always highly recommended.

Technical Data Sheet:

SILACRYL

WET LOOK & MATT FINISH



Description:

SILACRYL Wet Look is a high performance solvent based sealer, designed to beautify and protect masonry surfaces. Only quality acrylic resins are used in the manufacturing of **SILACRYL** to guarantee durability, UV Protection, and high gloss levels. **SILACRYL** is widely regarded as one of the best slate sealing products on the market.

Advantages:

- Suitable for internal and external use
- Gives a wet look (gloss or matt) which enhances the natural colours of the surfaces, like slate and sandstone
- Seals against food, soils, grease, oil and inhibits staining
- Seals Limestone dust into concrete to prevent leaching and a constant need for sweeping
- Available in Gloss or Matt finish
- Is easy to reseal without stripping
- Does not yellow externally
- Australian owned and manufactured in Australia

Characteristics:

Colour:	Clear
Weight:	0.90
Solvent:	Hydrocarbon
DG Class:	3
U.N Number:	1263
Coverage:	8 – 10 sq m per lt (depending on porosity)

Recommendations:

Sandstone
Slate
Masonry blocks
Granite
Brickwork
Concrete pavers

Disclaimer User Guide

*Solutions - Sealers for Stone & Tile believes the information contained in this document is accurate as **general advice only**. As general advice only it has been prepared without taking into account the objectives, problems or needs of the reader. Solutions . Sealers for Stone & Tile has presented this information as a guide only and accepts no liability for any loss or damage caused by any error in, or omission from, this document. Solutions . Sealers for Stone & Tile has no control over the use or misuse of this product, therefore no warranty expressed or implied shall be given. Solutions . Sealers obligations shall be limited to only replacing product PROVEN defective. The user **MUST** educate themselves on the performance value, application rates, substrate type and environment before product is applied, a TEST area is always highly recommended.*